Saskatchewan Manlift Certification

Saskatchewan Manlift Certification - The Manlifts and Elevated Platforms program provides training on the rules, regulations and correct application of safe operating measures and work practices included in daily activities for individuals who work utilizing this equipment. The course has been designed for individuals who are actively involved in these activities or individuals who have a basic understanding of this equipment.

In the past couple of decades, aerial platforms and manlifts have become a common sight in industrial maintenance applications and on construction job sites. These machinery provide an easy way to lift staff close to what must be carried out on a stable platform apparatus, allowing workers to perform tasks with greater safety and comfort rather than being perched on top of scaffolding or ladders.

Similar to every other tool, manlifts are just safe when they are utilized correctly. Since they elevate employees above ground level or floor, accidents can occur easily and this might cause serious death or injuries for both the manlift operators and any passerby who may not be lucky enough to be standing below.

Manlifts come in a variety of types. The majority fit into 1 or 2 categories: the scissor lift, that is capable of moving upward and downward and the articulating boom lift, which could move both horizontally and vertically.

Protecting Workers

Right training is essential in regard to safety matters. A lot of the companies that rent manlifts would offer training at the jobsite. Each and every worker who would be working on the equipment or operating it must receive training in safe operations. It is likewise essential that only those employees who have received training should be authorized to operate the controls. Communication rules and operating procedures must be clear. Therefore, staff on the ground should not operate controls without the knowledge and approval of any staff inside the basket.

Those staff who would be occupying the basket are required to wear right fall protection such as lanyard and a harness. That protection must be connected to the manlift itself and not to a surface nearby. The worker must ensure that he or she has made whichever adjustments needed to reflect the change in fall distance if there are changes in the height of the work area.

To make sure that the manlift is in good operating condition, manlifts should be tested and inspected each day. Prior to making use of the equipment, whichever defects have to be re-inspected and repaired.